



Quaker State® Multi-Vehicle Automatic Transmission Fluid EXCEPTIONS

Always Check Specification Manual, owner's manual and/or dipstick for proper fluid type

Directions for using chart:

1. Locate the vehicle year, make and model in the **current Lubrication Recommendations and Capacities Guide or check vehicle owner's manual**. Note the manufacturer's specified fluid or part number.
2. Refer to following charts. If transmission fluid type or vehicle is listed below, only use the product listed or Original Equipment Manufacturer (OEM) fluid.

Quaker State® Multi-vehicle ATF EXCEPTIONS by Fluid Specification / General Application

Continuously Variable Transmissions (CVTs)	General Motors DEXRON®-VI ATF
Sealed "Fill For Life" transmissions	Nissan Matic K ATF
Ford TYPE F ATF	Toyota/Lexus Type WS ATF
Ford MERCON® SP, MERCON® LV, MERCON® C	

Quaker State® Multi-vehicle ATF EXCEPTIONS by Vehicle Application

This chart contains the latest information available at the time of publication of this bulletin and is believed to be current and accurate. SOPUS makes no claim or warranties regarding the accuracy or reliability of this information and is not responsible for any errors or omissions by original manufacturers. Responsibility for proper selection and application rests with the installer

<p>AM General (Hummer) 2006 and later; use Quaker State® DEXRON®-VI ATF</p>	<p>Ford/Lincoln/Mercury Trucks 2005 - 06 Econoline Vans with 5R110W 5-Speed Transmission; use MSP # XT-6-QSP (MERCON SP FLUID) 2003-07 5R110W (TorqShift) 5-Speed; use MSP # XT-6-QSP 2005-07 ZF 6HP26 6-Speed; use MSP # XT-6-QSP 2006-07 6R60 & 6R75; use MSP # XT-6-QSP</p>
<p>Audi 2003 -2007 Audi TT</p>	<p>Honda/Acura/Sterling/Isuzu All CVT applications; use Honda Genuine CVT Fluid</p>
<p>BMW 6-series or 7-series with 6-speed Automatic transmission GA6HP19Z, GA6HP26Z, GA6HP32Z, or S6S53BZ; use Shell ATF M-1375.4</p>	<p>Hummer (AM General) 2006 and later; use Quaker State® DEXRON®-VI ATF</p>
<p>Buick 2006 and later; use Quaker State® DEXRON®-VI ATF</p>	<p>Infiniti 2002-05 Q45 (SLF); use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2003 - 04 M45 (SLF); use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2006 M35, M45 (SLF); use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P</p>
<p>Cadillac 2006 and later; use Quaker State® DEXRON®-VI ATF</p>	<p>Jaguar 1998-2003.5 XJ series with 4.0L supercharged engine; use Shell ATF 3403 M115 2003.5 and later XJ series with 3.0L, 3.5L, 4.2L and 4.2L supercharged engine; use Shell M1375.4 1998-2003 XK series with 4.0L supercharged engine; use Shell ATF 3403 M115 2003 and later XK series with 4.2L and 4.2L supercharged engine; use Shell M1375.4 2004-2006 XKR; use Shell ATF 3403 M115 2002.5-06 S-Type; use Shell ATF M-1375.4 2001.5-06 X-Type; use automatic transmission fluid ATF IDEMITSU K17 (Jatco 3100PL085)</p>
<p>Chevrolet/GMC 2006 and later; use Quaker State® DEXRON®-VI ATF Exception: ok to use MV-ATF in AISIN (81-40LE) and AF33-5 transaxles</p>	
<p>Chrysler, Dodge & Plymouth Sprinter Van & 2004 - 06 NAG1 5 Speed SLF; use Shell 3403 only 2004 -2006 Crossfire; use Shell 3403 only</p>	
<p>Dodge Trucks Sprinter Van & 2003 - 06 NAG1 5 Speed (Sprinter Van) SLF, use Shell 3403 only</p>	
<p>Ford/Lincoln/Mercury Cars All Ford Escape (Hybrid), Mercury Mariner (Hybrid); (CVT) 2005 - 2007 Ford 500 (CVT), Freestyle (CVT); use VTF P/N XT-7-QCFT, Spec. WSS-M2C933-A (CFT30 Transmission only) 2005-2007 Mercury Montego (CVT); use VTF P/N XT-7-QCFT, Spec. WSS-M2C933-A (CFT30 Transmission only)</p>	

Quaker State® Multi-vehicle ATF EXCEPTIONS by Vehicle Application

This chart contains the latest information available at the time of publication of this bulletin and is believed to be current and accurate. SOPUS makes no claim or warranties regarding the accuracy or reliability of this information and is not responsible for any errors or omissions by original manufacturers. Responsibility for proper selection and application rests with the installer

<p>Jeep 2004 and later Grand Cherokee with NAG1 (5-speed); use Shell 3403 ATF 2007 Compass and Patriot (CVT); use Mopar CVT+4</p>	<p>Nissan 1998-2007 Nissan Murano; use Nissan CVT fluid NS-2 2004-06 Altima, Maxima; use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2004-07 Quest; use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2003-06 350Z; use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2004 Pathfinder Armada; use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2005 Armada; use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2005-06 Xterra; use NISSAN Matic K transmission fluid, P/N 99MP-MTK00P 2007 Altima (with CVT), Maxima (with CVT); use genuine Nissan CVT fluid NS-2 Versa (with CVT); use genuine Nissan CVT fluid NS-2</p>
<p>Land Rover 2005-06 LR3 with ZF 6HP26 Automatic Transmission; use Shell ATF M-1375.4 2006-07 Range Rover, Range Rover Sport; use Shell ATF M-1375.4; 2006 All Models; use Texaco N402 2002-06 Freelander (Jatco Automatic Transmissions), use Texaco N402 GM Auto transmissions; use Texaco ETL-7045E</p>	<p>Pontiac 2006 and later models (excluding Vibe); use Quaker State® DEXRON®-VI ATF</p>
<p>Lexus 2004 - 2007 LS430, LX470, GX470; use Toyota Genuine ATF WS (JWS3324 or NWS9638) 2007 ES350, GS350, GS430, GS450H, IS250, IS350; use Toyota Genuine ATF WS (JWS3324 or NWS9638) 1998-07 RX350, RX400H; use Toyota Genuine ATF WS (JWS3324 or NWS9638)</p>	<p>Porsche 2001-06 911 Turbo; use Shell ATF 3403-M115, Porsche P/N 000 043 204 41 2002-05 911 GT2; use Shell ATF 3403-M115, Porsche P/N 000 043 204 41 2006-07 911; use Porsche P/N000 043 30400</p>
<p>Mazda All Mazda Tribute (Hybrid) (CVT) 2004 RX8 (SJ6A-EL transaxle only)</p>	<p>Saab 2003-07 9-3 models with 6-speed; use Saab P/N 93 165 147 2005-07 9-7X; use Quaker State® DEXRON®-VI ATF</p>
<p>Mazda/Mercury Trucks 5R110W 5-Speed; use MSP # XT-6-QSP (MERCON SP)</p>	<p>Saturn 2006-07 Vue, Ion (with dipstick); use Quaker State® DEXRON®-VI ATF 2002-07 Vue (CVT) (no dipstick); use DEX-CVT® Fluid, Saturn P/N 22688912 and DEX-CVT® Fluid Additive, Saturn P/N 22697447 2003-07 Ion (CVT) (no dipstick); use DEX-CVT® Fluid, Saturn P/N 22688912 and DEX-CVT® Fluid Additive, Saturn P/N 22697447 2006-07 Relay; use Quaker State® DEXRON®-VI ATF 2007 Aura; use Quaker State® DEXRON®-VI ATF 2007 Sky; use Quaker State® DEXRON®-VI ATF</p>
<p>Mini 2002-06 Cooper (CVT); use Esso CVT EZL 799 Fluid, MINI P/N 83 22 0 136 376 2005+ Cooper S (6 speed Auto); use Mini ATF JWS 3309, MINI P/N 83 22 0 402 413</p>	<p>Toyota 2007 Camry, Yaris, FJ Cruiser; use Toyota Type WS fluid only 2005-07 Avalon, Tundra; use Toyota Type WS fluid only 2004 4-Runner (5-speed); use Toyota Type WS fluid only 2005-07 4-Runner, Sequoia; use Toyota Type WS fluid only 2006-07 Highlander (Hybrid), Rav4; use Toyota Type WS fluid only 2004-07 Land Cruiser, LX470; use Toyota Type WS Fluid only 2004 - 07 Prius; use Toyota Type WS fluid only 2004 - 06 Toyota Transmission # A750E, A750F; use Toyota Type WS Fluid only</p>
<p>Mercedes-Benz 1996-99 5-speed (W5A580 model 722.6); use Mercedes-Benz P/N 001 989 21 03 10 (Shell ATF 3403-M 115 or ATF 134/ATF 3353) 1998-2006 All models with Flexible Service System (FSS); use Mercedes-Benz P/N 001 989 21 03 10 (Shell ATF 3403-M 115) 2003+ 7-speed Mercedes-Benz; Shell ATF 134 (or ATF 3353 if available)</p>	