

Filling Tank



IMPORTANT!!!!
DO NOT FILL SOLUTION TANK WITH BUCKET. DEBRIS CAN BE PRESENT IN THE BUCKET, WHICH CAN IN TURN ENTER THE PUMP AND CAUSE CLOGS OR DAMAGE!



To fill solution tank use a hose or other source of direct clean water.

Empty Front Tank



To empty front tank, insert hand tool with vacuum on and heater off into front solution tank and vacuum up remaining solution. Solution can then be easily drained by rear drain valve. When doing this remember not to depress the solution lever on hand tool because recycling of solution will then occur.



Heater Circuit Breaker

The Tech 3000 is equipped with a circuit breaker on the heater unit to prevent damage the heater and the machine. There are many things that can trigger the heater circuit breaker to pop.

- Turning the heater on with no water in the tank or running the unit dry can cause it to pop.
- Running chemical that is not intended for use in extractor machines can coat the coils in the heater and over time will cause heater damage. Use only chemicals made for use in extractors.
- When finished with machine, turn off all switches THEN unplug. Just unplugging machine can cause power surges and damage machine.



The circuit breaker for the heater in the Tech 3000 units are located on the left side of the machine (if you are standing behind the machine) about 3 inches up from the front of the rear wheel.



To reset the heater circuit breaker remove the plug from the side of the machine using a flathead screwdriver or your finger nail and take a long thin object such as a pencil or long sturdy paper clip and insert it into the hole. The circuit breaker should be right behind the hole, however due to shifting during use or shipping, it may be off center. You may need to feel around for it.

Machine Maintenance



Use lubricant to prevent sticking on drain valve. Spray the handle rod and the inside of drain valve.



Hand Tool Maintenance



Lube the valve on the hand tool as well as the quick connect on the rear of the machine where the hand tool hose connects to the machine.



Machine Care



When moving machine around, do not pull by cord. Grasp the handles and move the machine that way. Pulling cord can cause damage to machine.

Machine Information



If making a warranty claim or ordering parts for machine, have serial number as well as model number available. This information can be located on the rear of the machine on a sticker as seen in the picture.